


Tileform UK Ltd


Tactray 90 Structural Liner Tray Load / Span Tables

Thickness mm	Weight Kg/m ²
0.75	8.83
1.00	11.78
1.25	14.72
1.50	17.35

Load factor (working load to ultimate) = 1.5



Tables indicate total load carrying capacity of tray - Tables do not include self weight of tray



TileformUK:06/2010

Working Load UDL (kN/m²) - Gravity Deflection L/150 Consider when Tactray 90 is supporting metal wall cladding products

Thickness (mm)	Span Condition	Span (M)																									
		1.60	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	4.60	4.80	5.00	5.20	5.40	5.60	5.80	6.00	6.20	6.40	6.60
0.75	Single	2.57	2.28	2.05	1.87	1.71	1.58	1.47	1.37	1.28	1.21	1.14	1.08	0.99	0.87	0.78	0.70	0.63	0.57	0.52	0.47	0.43	0.40	0.37	0.34	0.31	0.29
1.00	Single	4.61	4.09	3.69	3.35	3.07	2.83	2.63	2.46	2.30	2.17	2.05	1.88	1.70	1.54	1.40	1.28	1.17	1.08	0.99	0.91	0.85	0.78	0.73	0.68	0.64	0.58
1.25	Single	7.19	6.39	5.75	5.23	4.79	4.42	4.11	3.83	3.59	3.22	2.87	2.58	2.32	2.11	1.92	1.75	1.60	1.47	1.36	1.25	1.16	1.08	0.97	0.88	0.80	0.73
1.50	Single	10.30	9.16	8.24	7.49	6.87	6.34	5.86	5.12	4.50	3.99	3.56	3.20	2.89	2.62	2.39	2.19	2.01	1.85	1.71	1.58	1.44	1.30	1.17	1.06	0.97	0.88
0.75	Double	2.39	2.02	1.73	1.50	1.31	1.16	1.03	0.93	0.84	0.76	0.69	0.63	0.58	0.54	0.50	0.46	0.43	0.40	0.37	0.35	0.33	0.31	0.29	0.28	0.26	0.25
1.00	Double	4.16	3.51	3.00	2.60	2.28	2.02	1.80	1.61	1.45	1.32	1.20	1.10	1.01	0.93	0.86	0.80	0.74	0.69	0.65	0.61	0.57	0.54	0.51	0.48	0.45	0.43
1.25	Double	6.12	5.15	4.40	3.80	3.33	2.94	2.61	2.34	2.11	1.91	1.74	1.59	1.46	1.34	1.24	1.15	1.07	1.00	0.93	0.87	0.82	0.77	0.73	0.69	0.65	0.61
1.50	Double	8.39	7.04	6.01	5.19	4.53	4.00	3.55	3.18	2.86	2.59	2.35	2.15	1.97	1.82	1.68	1.56	1.45	1.35	1.26	1.18	1.11	1.04	0.98	0.92	0.87	0.83
0.75	Multi	2.83	2.39	2.05	1.79	1.57	1.39	1.24	1.11	1.01	0.91	0.83	0.76	0.70	0.65	0.60	0.56	0.52	0.49	0.45	0.43	0.40	0.38	0.36	0.34	0.32	0.30
1.00	Multi	4.92	4.16	3.57	3.10	2.72	2.41	2.15	1.93	1.75	1.59	1.45	1.33	1.22	1.13	1.04	0.97	0.90	0.84	0.79	0.74	0.70	0.66	0.62	0.58	0.55	0.52
1.25	Multi	7.25	6.12	5.24	4.54	3.98	3.52	3.14	2.81	2.54	2.30	2.10	1.92	1.77	1.63	1.51	1.40	1.30	1.21	1.14	1.06	1.00	0.94	0.89	0.84	0.79	0.75
1.50	Multi	9.95	8.38	7.17	6.21	5.43	4.80	4.27	3.82	3.45	3.13	2.85	2.60	2.39	2.20	2.04	1.89	1.76	1.64	1.53	1.44	1.35	1.27	1.20	1.13	1.07	1.01

Working Load UDL (kN/m²) - Uplift Deflection L/150 Consider when Tactray 90 is supporting metal wall cladding products

Thickness (mm)	Span Condition	Span (M)																									
		1.60	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	4.60	4.80	5.00	5.20	5.40	5.60	5.80	6.00	6.20	6.40	6.60
0.75	Single	2.57	2.28	2.05	1.87	1.71	1.58	1.45	1.26	1.11	0.98	0.88	0.79	0.71	0.65	0.59	0.54	0.49	0.46	0.42	0.39	0.36	0.34	0.32	0.30	0.28	0.26
1.00	Single	4.61	4.09	3.69	3.35	3.07	2.83	2.52	2.19	1.93	1.71	1.52	1.37	1.23	1.12	1.02	0.93	0.86	0.79	0.73	0.68	0.61	0.55	0.49	0.45	0.41	0.37
1.25	Single	7.19	6.39	5.75	5.23	4.79	4.10	3.53	3.08	2.71	2.40	2.14	1.92	1.73	1.57	1.43	1.31	1.20	1.11	0.99	0.88	0.79	0.71	0.64	0.58	0.53	0.48
1.50	Single	10.30	9.16	8.24	7.49	6.39	5.44	4.69	4.09	3.59	3.18	2.84	2.55	2.30	2.09	1.90	1.74	1.56	1.38	1.23	1.10	0.98	0.89	0.80	0.73	0.66	0.60
0.75	Double	2.85	2.43	2.10	1.84	1.62	1.45	1.30	1.17	1.06	0.96	0.86	0.78	0.71	0.65	0.59	0.55	0.50	0.47	0.43	0.40	0.37	0.35	0.33	0.30	0.29	0.27
1.00	Double	4.74	4.03	3.48	3.04	2.68	2.38	2.14	1.92	1.74	1.59	1.45	1.33	1.23	1.14	1.06	0.98	0.92	0.85	0.80	0.75	0.70	0.66	0.62	0.59	0.55	0.52
1.25	Double	6.88	5.86	5.05	4.40	3.87	3.44	3.08	2.77	2.51	2.28	2.08	1.91	1.76	1.63	1.51	1.40	1.30	1.21	1.13	1.06	1.00	0.94	0.88	0.83	0.79	0.75
1.50	Double	9.11	7.72	6.64	5.78	5.08	4.51	4.03	3.62	3.27	2.97	2.72	2.49	2.29	2.12	1.96	1.82	1.70	1.59	1.48	1.39	1.30	1.23	1.15	1.09	1.03	0.97
0.75	Multi	3.33	2.85	2.47	2.17	1.92	1.71	1.54	1.39	1.26	1.14	1.03	0.94	0.85	0.78	0.72	0.66	0.61	0.56	0.52	0.48	0.45	0.42	0.40	0.37	0.35	0.33
1.00	Multi	5.56	4.75	4.11	3.60	3.18	2.83	2.54	2.29	2.08	1.90	1.74	1.60	1.48	1.37	1.27	1.18	1.10	1.03	0.96	0.90	0.85	0.80	0.75	0.71	0.67	0.62
1.25	Multi	8.11	6.92	5.98	5.22	4.60	4.10	3.67	3.31	3.00	2.73	2.50	2.30	2.12	1.96	1.82	1.69	1.57	1.47	1.37	1.29	1.21	1.14	1.07	0.97	0.88	0.81
1.50	Multi	10.76	9.15	7.89	6.88	6.06	5.38	4.82	4.34	3.93	3.57	3.27	3.00	2.76	2.56	2.37	2.20	2.06	1.92	1.80	1.69	1.58	1.48	1.33	1.21	1.10	1.00

Tileform UK Ltd
Spital Farm Offices, Thorpe Mead, Banbury, Oxon, OX16 4RZ Tel : 01295 250998 | Fax : 01295 271068 | www.britmet.co.uk | email : britmettileform@hotmail.com

This document is not intended to impose nor shall it be construed as imposing any legally binding obligation upon Tileform UK Ltd, Britmet Tileform Ltd and/or any of its associated companies. Due to a policy of continual development, Tileform UK Ltd reserves the right to alter any of the specifications given in this publication without prior notice.